# LUX SOLAR

LED FLOODLIGHTS | 4 X 65 W (IP69K) ILLUMINATED AREA | 2400 m<sup>2</sup>

VERTICAL TELESCOPIC MAST MAX HEIGHT | 8.5 m LIFETIME WARRANTY

BATTERY PACK | N.2 UNITS AGM 24V DC - 260 Ah EXPECTED OPERATION | 20 HRS

DEDICATED FRONTAL PANEL BATTERY CHARGER MANUAL | AUTO MODE LIGHT SENSOR



Ë

U

4

N.2 SOLAR PANEL WATTAGE | 330 W EACH



GALVANIZED METAL BODY 80 µm POWDER COATING









# Lux Green Series

#### **Dimensions & weight**

Dimensions min.	mm	3215 X 2040 X 2750
Dimensions max.	mm	3640 X 2600 X 8500
Total weight without fuel	Kg	785
Features		
Floodlight	W	4 X 65 W
Lamps type	W	Led
Floodlight IP level		69K
Mast Rotation		340°
Lifting method		Manual
Wind stability	km/h	80

MADE IN

ΙΤΔΙΥ

#### Solar Panel

Model		Monocrystal Silicon
Quantity	n	2
Wattage	W	330
Solar charger control		MPPT 100-30
Solar panels deployment		Manual - Fix Inclination 26°


### **Battery Pack**

Туре		AGM
Number of units	n	2
Battery Pack Power		24VDC – 260Ah
Expected battery cycles	n	500
Running Time	h	20
Charging time (Led Off)	h	9


### Loading Plan


Disassembled and stacked				
40' HC Container	15 Units			
20' Container	4 Units			
Truck	18 Units			


#### **Illuminated Area**



## TECHNICAL DATA









Luxtower: Via Strada Nuova, 28 - 27050 Codevilla (PV) ITALY | TLF. +39 0383 365544 | Fax +39 0383 49702

SUPER SILENT

NO MAINTENANCE

NO FUEL COSTS

NO EMISSIONS

LUXTOWER ongoing policy is in continuous improvement. The company reserves the right to modify the technical specifications and items described in this catalogue at any time and without notice for technical or commercial reasons. Product images are shown for information only LUXTOWER® - 2016© All rights reserved.